D3F28IP5MP



MINI VANDAL DOME CAMERA WITH HOMI OUTPUT



Elevate your security with our new security camera with HDMI output, featuring a 2.8mm lens and 5MP resolution for crystal-clear images. It offers flexible power options with DC 12V or PoE, while its intelligent face detection and customizable deterrence messages enhance security. With audio in/out capabilities, you can communicate seamlessly. Upgrade your surveillance and safeguard your store with confidence.

© CAMERA	
IP RATING	IP66
FILTER	Removable IR Cut Filter
IMAGE SENSOR	1/2.8" 5Mega-pixel Sony CMOS
PIXELS	2688(H)×1944(V)
HORIZONTAL RESOLUTION	5MP Max
LENS	2.8mm Fixed
IR RANGE	20 Meters
MIN ILLUMINATION	O Lux When IR ON
ELECTRONIC SHUTTER	NTSC:1/30-1/100,000s PAL:1/25-1/100,000s
• FUNCTION	
IMAGE SETTING	Contrast, Brightness, Sharpness, Saturation , WDR, 3DNR, HLC,BLC
STORAGE	NVR, VMS, TF Card
VIDEO TYPE	Manual, Timing, Motion Detection, Face Detection
ALARM TRIGGERS	Motion Detection, Al Face Detection

FACE DETECTION	HDMI OUTPUT
5MP RESOLUTION	2.8MM LENS
DC12V OR POE	AUDIO IN/OUT

Snapshot, Video, Alarm Output, Email Upload,

Flashing, Mirror, OSD information overlay, Camera angle, Banner

IE. Chrome, Firefox, Safari

CUSTOM DETERRENCE MESSAGE



ALARM EVENT

GENERAL FUNCTION

SYSTEM/EXPLORER SUPPORT

MONPVM-22



PVM POE **MONITOR**





Our innovative PVM Monitor boasts a range of features tailored for retail settings, including pre-recorded messages, reliable power supply, facial recognition, and more, all safeguarded by IK7 tempered glass protection. Paired with our HDMI Camera. equipped with two-way audio and alarm capabilities, it forms a comprehensive security system perfect for retail stores.



21,5" IK7 TEMPERED GLASS

CUSTOMIZABLE DISPLAY

WIFI & RJ45 CONNECTION

DC 12/24V OR POE POWERED

RECORDING	
RECORDING	Motion/Video Blind/Face/PIR Detection
TF CARD SLOT	1TB Max for Remote Recording
BRANDING LOGO	PNG Picture ALWAYS Show on PVM
WARNING MESSAGE	PNG Picture Based Pop-up
VOICE BROADCAST	WAV
SPEAKER	Built-in 3Wx2
WI-FI	Support, 2.4GHz, Auto On
PIP/PBP	YES
DISPLAY MODES	Full AD/Full IP Video/Banner/Switch (from AD to IP When Faces Detected)
BANNER MODE RATIO	IP:1200x1080 AD:720x1080
VIDEO OUTPUT	RJ 45x1 10M/100M

BUILT-IN NDAA IP CAMERA	
SOLUTION	2MP CMOS+8MP AI Chipset
MAX RESOLUTION	1920x1080
EMMC	8GB
DDR	1GB
H.264&265	Yes
ONVIF	Profile S
WEB BROWSER	IE, Chrome, Firefox, Safari
AI FUNCTION	Face Detection
PIR SENSOR	Yes

CUSTOM ADVERTISEMENT DEPLOY VIA MANAGEMENT SOFTWARE

RECORD DIRECTLY ON LOCAL NVR OR INTEGRATED 1TB SD CARD

BUILT TO RUN 24/7 OR WITH CUSTOMIZED WORK SCHEDULE